

Assembly and Installation Instruction

Warning!!! Shut Power Off At Fuse or Circuit Breaker .

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation.

2. For Model No. Z17-52P and Z17-53P

3. Attach two Mounting Screws to Mounting bracket and securing mounting bracket to Outlet box..

4. Thread the slip washer, knurl nut, threaded rod into the Mounting bracket, and screw the threaded rod onto the Ceiling canopy..

5. Connect the White Fixture Wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire.

Make sure all Wire Connectors are secure and do not easily pull off with the slight tug. Connect Ground Wire from the Outlet Box and Fixture Ground Wire to the Mounting Bracket with the Green Grounding Screw provided.

6. After the wires connected, raise Canopy against ceiling and tighten with Loop.

7. Connect the chain to the ceiling canopy and the fixture canopy..

8. Screw the socket assembly into the center rod.

9. Screw the threaded rod into the socket assembly.

10. Place the square metal washer ,shade over the end of the threaded rod and tighten with the rubber washer and finial securing the shade in place by using Hand Tool.

11. Attach the fixture arms to the fixture canopy and to the hooks inside the shade.

12. Insert Bulb to Socket. Return the power to the Outlet Box and test the fixture. Your installation is now complete.

